



Tomadas de Sobrepor

Dimensões

IP44 - 16 A, 32 A



Referências	Dimensões										
	a	b	c	d	d1	e	f	g	h	M	M*
TSW-16P3H4E10											
TSW-16P3H6E57	87	62	110	40	-	50	4,5	4	115	20	M20
TSW-16P3H9E53											
TSW-32P3H4E10											
TSW-32P3H6E57	128	71	147	11	-	68	5,3	4	158	32	M32
TSW-32P3H9E53											
TSW-16P4H4E10											
TSW-16P4H6E53	100	67	125	-	11	59	5	4	118	20	M20
TSW-16P4H9E57											

Referências	Dimensões										
	a	b	c	d	d1	e	f	g	h	M	M*
TSW-32P4H4E10											
TSW-32P4H6E53	128	71	147	11	-	68	5,3	4	158	32	M32
TSW-32P4H9E57											
TSW-16P5H4E10											
TSW-16P5H6E53	100	67	131	-	11	59	5	4	128	20	M20
TSW-16P5H9E57											
TSW-32P5H4E10											
TSW-32P5H6E53	128	71	152	11	-	68	5,3	4	160	32	M32
TSW-32P5H9E57											



Referência	TSW-16P4H4E10	TSW-16P4H9E57	TSW-16P4H6E53	TSW-32P4H4E10	TSW-32P4H9E57	TSW-32P4H6E53
Código	12822059	12822073	12822087	12822063	12822077	12822109
Corrente (A)	16	16	16	32	32	32
Número de polos	4 (3P+T)			4 (3P+T)		
Posição pino terra / cor	4H	9H	6H	4H	9H	6H
Tensão nominal	100-130 V	200-250 V	380-440 V	100-130 V	200-250 V	380-440 V
Grau de proteção	IP44			IP44		
Seção transversal (mm²)	1,5 - 2,5			4 - 6		